

MASONRY DRILLING
DRILLING & CUTTING PRODUCTS

CARBIDE REBAR CUTTERS


**MADE
IN THE
USA**

CARBIDE REBAR CUTTERS

SERIES RBC
1/2" STRAIGHT SHANK

PART NUMBER	SIZE	O/A LENGTH	SUGGESTED RPM's	PRICE EACH
RBC0838	3/8"	8"	850-1200	\$43.13
RBC1212	1/2"	12"	850-1200	\$45.52
RBC1916	9/16"	12"	850-1200	\$47.93
RBC1258	5/8"	12"	750-1000	\$59.90
RBC1858	5/8"	18"	750-1000	\$79.07
RBC1116	11/16"	12"	750-1000	\$64.70
RBC1234	3/4"	12"	600-850	\$67.09
RBC1834	3/4"	18"	600-850	\$88.65
RBC1316	13/16"	12"	600-850	\$81.46
RBC1278 *	7/8"	12"	600-850	\$95.84
RBC1201 *	1"	12"	500-750	\$103.03
RBC1218 *	1-1/8"	12"	500-750	\$110.22
RBC1214 *	1-1/4"	12"	450-600	\$117.41
RBC1238 *	1-3/8"	12"	450-600	\$129.39
RBC1112 *	1-1/2"	12"	350-500	\$136.58
RBC1134 *	1-3/4"	12"	350-500	\$158.14
RBC1202 *	2"	12"	350-500	\$268.36
RBC1222 *	2-1/2"	12"	350-500	\$316.28

* Sizes 7/8" to 2-1/2" have threaded, screw-on (replaceable) heads. Exchange heads with any of the below extensions.

PART NUMBER	SIZE	PRICE EACH
RBCS-1212	12" REBAR SHANK (1/2" - 13)	\$17.52
RBCS-1234	12" REBAR SHANK (3/4" - 10)	\$17.52
RBCS-1812	18" REBAR SHANK (1/2" - 13)	\$24.45
RBCS-1834	18" REBAR SHANK (3/4" - 10)	\$24.45
RBCS-2412	24" REBAR SHANK (1/2" - 13)	\$32.58
RBCS-2434	24" REBAR SHANK (3/4" - 10)	\$32.58
RSDS-1212	12" SDS-PLUS SHANK (1/2" - 13)	\$21.60
RSDS-1234	12" SDS-PLUS SHANK (3/4" - 10)	\$21.60
RSDS-1812	18" SDS-PLUS SHANK (1/2" - 13)	\$30.25
RSDS-1834	18" SDS-PLUS SHANK (3/4" - 10)	\$30.25
RSDS-2412	24" SDS-PLUS SHANK (1/2" - 13)	\$40.35
RSDS-2434	24" SDS-PLUS SHANK (3/4" - 10)	\$40.35

What to do when you encounter rebar:

- 1) **STOP DRILLING!!!** The sound of a rotary hammer or a carbide hammer drill bit hitting steel is much higher than when cutting concrete.
- 2) Remove the drill bit from the hole.
- 3) Mount a rebar cutter of the same diameter as the hole in either a standard 1/2" drill motor, or a 1/2" rotary percussion drill with the selector in the "rotary only" position.
- 4) Insert the rebar cutter into the hole and begin drilling at the suggested RPM speed only. Apply just enough pressure to grind away at the rebar. **Do Not Use Excessive Speed or Pressure on the Machine** - this will either damage or break the rebar cutter.
- 5) Once rebar is cut through, remove the rebar cutter from the hole and continue drilling with a rotary hammer or carbide hammer drill bit.

- Carbide cutters are brazed in place to keep Rebar Cutter from enlarging existing hole.

SIZES

 7/8" → 1-3/4"
 2" → 2-1/2"

THREAD

 1/2"-13
 3/4"-10

REMINDER:

Rebar Cutters are problem solvers only. A 1/2" Rebar Cutter drilling through #6 (3/4") rebar dead center **may** result in 5 to 10 holes being drilled provided correct speed and pressure are utilized. It is not uncommon for only one piece of rebar to be cut per Rebar Cutter. Rebar Cutters *should not* be used for drilling concrete.

Rebar Cutters are not warrantied for replacement or repair.