

**SECURITY FASTENERS**
**SECURITY PRODUCTS**

# One-Way Tamper-Resistant Screws

## One-Way

One-Way screws are available in a round head design in both machine and sheet metal type in sizes ranging from #6 to #14. They are slotted screws, and can be installed with a standard slotted screwdriver. However, removing them without the proper tool is difficult. Half of each side of the slot is smoothed down during manufacture. When you try to extract the screw, the slotted screwdriver tip will not grip and rides out of the slot. The screws are case hardened and zinc plated.



### One-Way Round Head Case Hardened Zinc Plated

#### Machine Screws

ITEM	SIZE BOX CODE
OWY-0632025Z	#6-32 x 1/4"
OWY-0632050Z	#6-32 x 1/2"
OWY-0632075Z	#6-32 x 3/4"
OWY-0632100Z	#6-32 x 1"
OWY-0632150Z	#6-32 x 1-1/2"
OWY-0832050Z	#8-32 x 1/2"
OWY-0832075Z	#8-32 x 3/4"
OWY-0832100Z	#8-32 x 1"
OWY-0832150Z	#8-32 x 1-1/2"
OWY-1024050Z	#10-24 x 1/2"
OWY-1024075Z	#10-24 x 3/4"
OWY-1024100Z	#10-24 x 1"
OWY-1024125Z	#10-24 x 1-1/4"
OWY-1024150Z	#10-24 x 1-1/2"
OWY-1032050Z	#10-32 x 1/2"
OWY-1032075Z	#10-32 x 3/4"
OWY-1032100Z	#10-32 x 1"
OWY-1032150Z	#10-32 x 1-1/2"
OWY-2520050Z	1/4"-20 x 1/2"
OWY-2520075Z	1/4"-20 x 3/4"
OWY-2520100Z	1/4"-20 x 1"
OWY-2520150Z	1/4"-20 x 1-1/2"
OWY-2520200Z	1/4"-20 x 2"
OWY-2520300Z	1/4"-20 x 3"

#### Sheet Metal Screw

ITEM CODE	SIZE
OWY-06037Z	#6 x 3/8"
OWY-06050Z	#6 x 1/2"
OWY-06075Z	#6 x 3/4"
OWY-06100Z	#6 x 1"
OWY-06125Z	#6 x 1-1/4"
OWY-08037Z	#8 x 3/8"
OWY-08050Z	#8 x 1/2"
OWY-08075Z	#8 x 3/4"
OWY-08100Z	#8 x 1"
OWY-08125Z	#8 x 1-1/4"
OWY-08150Z	#8 x 1-1/2"
OWY-08200Z	#8 x 2"
OWY-10050Z	#10 x 1/2"
OWY-10075Z	#10 x 3/4"
OWY-10100Z	#10 x 1"
OWY-10125Z	#10 x 1-1/4"
OWY-10150Z	#10 x 1-1/2"
OWY-10200Z	#10 x 2"
OWY-12050Z	#12 x 1/2"
OWY-12075Z	#12 x 3/4"
OWY-12100Z	#12 x 1"
OWY-12125Z	#12 x 1-1/4"
OWY-12150Z	#12 x 1-1/2"
OWY-12200Z	#12 x 2"
OWY-14050Z	#14 x 1/2"
OWY-14075Z	#14 x 3/4"
OWY-14100Z	#14 x 1"
OWY-14150Z	#14 x 1-1/2"
OWY-14200Z	#14 x 2"
OWY-14250Z	#14 x 2-1/2"
OWY-14300Z	#14 x 3"

## Sex Bolts

Architectural Series Sex Bolts have smooth truss heads with no drive. These parts are tamper-resistant, as there is no way to turn the sex bolt without a drive in the head. The knurled barrel keeps the sex bolt from spinning while the flat head screw is tightened from the other side. A mating 1/4"-20 x 1" flat machine screw is supplied to match the finish on the sex bolt.



### Architectural Series Sex Bolts



ITEM CODE	BARREL LENGTH	THREAD SIZE	THREAD DEPTH	HEAD DIAMETER	HEAD HEIGHT	MATERIAL	BOX QTY.
SXB-2520100Z*	1-9/16"	1/4"-20	1"	9/16"	5/32"	Steel Zinc Plated	25
SXB-2520075S*	1-9/16"	1/4"-20	3/4"	9/16"	5/32"	Stainless Steel	25
SXB-2520125B*	1-9/16"	1/4"-20	1-1/4"	9/16"	5/32"	Brass	25
SXB-2520100A*	1-9/16"	1/4"-20	1"	9/16"	5/32"	Aluminum	25

### Female Tamper-Resistant Barrel-Nuts



ITEM CODE	HEAD STYLE	BARREL DIAMETER	THREAD SIZE	BARREL LENGTH	DRIVER SIZE	MATERIAL	BOX QTY.
FTB-1024050-ROC	Round Head One-Way	1/4"	#10-24	1/2"	*	Steel Chrome Plated	100
FTB-1024062-ROC	Round Head One-Way	1/4"	#10-24	5/8"	*	Steel Chrome Plated	100
FTB-1024075-BTS	Button Torx-Security	1/4"	#10-24	3/4"	#27	Stainless Steel	100
FTB-1024087-FTS	Flat Torx-Security	1/4"	#10-24	7/8"	#30	Stainless Steel	100
FTB-3125075-BTS	Button Torx-Security	3/8"	5/16"-18	3/4"	#45	Stainless Steel	50
FTB-3125100-FTS	Flat Torx-Security	3/8"	5/16"-18	1"	#45	Stainless Steel	50

### Male Tamper-Resistant Shoulder Screws



ITEM CODE	HEAD STYLE	SHOULDER DIAMETER	THREAD SIZE	THREAD LENGTH	MATERIAL	BOX QTY.
TRS-1024075C	One-Way	1/4"	#10-24	3/4"	Steel Chrome Plated	100
TRS-10241516C	One-Way	1/4"	#10-24	15/16"	Steel Chrome Plated	100
TRS-102411SC	One-Way	1/4"	#10-24	1-1/16"	Steel Chrome Plated	100
TRS-10241316C	One-Way	1/4"	#10-24	1-3/16"	Steel Chrome Plated	100
TRS-10241516C	One-Way	1/4"	#10-24	1-5/16"	Steel Chrome Plated	100

\*Note: Architectural Series Sex Bolts - Packaged 100 per box - Bulk carton available.